

www.kingstonbrass.com

TOLL-FREE CUSTOMER SERVICE: 1-877-2-KBRASS

TECHNICAL SUPPORT E-mail: service@kingstonbrass.com

12775 Reservoir Street, Chino, CA 91710

KINGSTON


KITCHEN & BATH

INSTALLATION INSTRUCTIONS Brass Tub Bath Drain

Note: 1. Observe all local plumbing and building codes.

- 2. Inspect waste and supply tubing; replace if necessary.
- 3. If you are installing a new bath, install the drain before installing the bath. Refer to the manufacturer's installation instructions.
- 4. Adjustable pop-up drain has removable parts.

TOOLS REQUIRED



Tub_Surface_

Rubber Washer (10)

Waste Tube(9" Long) (9)

INSTALLATION INSTRUCTIONS:

- 1. Place rubber washer (10) onto waste tube (9) and set them under the tub.
- 2. Apply Teflon tape on strainer thread and a bead of silicone sealant under waste strainer (11) and thread into waste tube (9), wipe off excess sealant.
- 3. Attach Plunger mechanism to overflow cover plate with the aid of the cotter pin (13).
- 4. Place rubber gasket (3) on overflow tube, hold to the back of the tub at the overflow opening.
- Insert plunger mechanism with the attached cover plate from inside the tub into the overflow tube.
 Secure by attaching cover plate to overflow tube using the two machine screws.
- 6. Adjust linkage so that in a close position plunger fit snug inside seat of tee.
- 7. Slip joint nuts (5) and plastic washers (6) onto overflow tube (4) and waste tube (9).
- 8. Apply Teflon tape to the two threads on three way tee (7) and the thread on drain tube (8).
- 9. Slip on tee onto both the waste tube (9) and overflow tube (4), adjust to desired location and tighten slip joint nut.
- 10. Thread on drain tube (8) and make the necessary connection to your drain system.
- 11. Fill tub with water, sufficient to cover the overflow cover plate (2), check for leaks and retighten any connections as necessary.

