



<p>Record your model number.</p>	<p>Observe all local plumbing and building codes.</p>	<p>⚠ CAUTION: Risk of personal injury. Product can break, chip, and cause injury if handled carelessly. Get help lifting the bathroom sink.</p>	<p>Do not substitute another sealant if one is supplied with the sink.</p>	<p>This sink is recommended for use with a wall-mount faucet.</p>
<p>1 Position the sink on the countertop.</p>	<p>For Wall-Mount Faucet: Provide sufficient spout overhang into the sink bowl.</p>	<p>For Countertop Faucet: Provide adequate spout and handle clearance when locating the faucet. Refer to the faucet installation instructions for required clearance, and mark the preferred faucet hole locations.</p>	<p>2 Trace the drain opening on the countertop.</p>	<p>3 Mark the center of the drain opening and drill a 3-3/4" (95 mm) hole at the center mark.</p>
<p>4 Temporarily set the sink into the countertop cutout and check for fit.</p>	<p>5 Remove the sink from the countertop cutout.</p>	<p>6 Install the faucet according to the manufacturer's instructions.</p>	<p>7 Apply a bead of adhesive sealant around the drain hole.</p>	<p>8 Place the sink over the drain hole, and wipe away any excess sealant. Allow the sealant to cure before installing the drain.</p>
<p>9 Install the drain according to the manufacturer's instructions, and complete the faucet and drain connections.</p>	<p>10 Run water and check for leaks.</p>			

Questions? Problems? For additional assistance, please contact
KALLISTA's Customer Service Department at 1-888-4-KALLISTA
(1-888-452-5547) or kallista.com.