STERLING
A KOHLER COMPANY

Features
- Alcove installation
- 17-1/4" apron
- Solid Vikrell material
- Right drain
- Pivot snap-together modular design
- Smooth, high-gloss walls
- No caulk required
- Four corner shelves
- Stainless steel grab bars and bath seat

Included Components
Product consists of:
  71244123 60" x 30" ADA Wall Set with Grab Bars
  71141124 60" x 30" ADA Bath

ADA

Codes/Standards
CSA B45.5/IAPMO Z124
ASTM E162
ASTM E662
Greenguard UL 2818 - Gold
ADA
ICC/ANSI A117.1
HUD, UM Bulletin 73

Warranty – Bathing Fixtures (and) Kitchen and Utility Sinks Made of Solid Vikrell® Material
STERLING® Warranty - Grab Bars
STERLING® Warranty - Bathing & Showering Seats
See website for detailed warranty information.

Available Colors/Finishes
Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	KOHLER Biscuit

1-800-STERLING (1-800-783-7546)
Kohler Co. reserves the right to make revisions without notice to product specifications.
For the most current Specification Sheet, go to www.sterlingplumbing.com.
4-26-2019 00:31 - US

6" (152 mm) (Typical)

14" (356 mm)

30" (762 mm)

16" (406 mm)

2" (51 mm) Min Drain Hole Clearance Through Wall

31-1/4" (794 mm)

30" (762 mm)

8" (203 mm)

15-1/4" (387 mm)

22-1/4" (565 mm)

59-3/8" (1508 mm)

3" (76 mm)

1-1/4" (32 mm)

31-1/4" (794 mm)

Ø 2" (51 mm) Drain

8" (203 mm)

55" (1397 mm)

3-1/2" (89 mm)

10" (254 mm)

4" (102 mm)

75-1/2" (1918 mm)

60-1/8" (1527 mm) Min
60-1/4" (1530 mm) Max

9" (229 mm)

57" (1448 mm)

Drain Detail

6-3/8" (162 mm)

3-5/8" (92 mm)

11-5/8" (295 mm)

36" (914 mm)

39" (991 mm)

21-1/4" (540 mm)

17-1/4" (438 mm)

60" (1524 mm)

20-1/4" (514 mm)

3" (76 mm) Drain Bottom to Floor

Technical Information
All product dimensions are nominal.

Installation:	Three-wall alcove, Seated alcove
Drain location:	Right
Basin area, bottom:	46-1/4" x 20-1/2" (1175 mm x 521 mm)
Basin area, top:	52-1/4" x 22-1/2" (1327 mm x 572 mm)
Water depth:	11" (279 mm)
Water capacity:	34 gal (128.7 L)
Maximum door height:	56-3/4" (1441 mm)
Maximum door width:	56-1/2" (1435 mm)

Notes
Install this product according to the installation instructions.

Product is designed to be used with a single-hole mixer valve with an escutcheon cover not to exceed 7-3/4" (197 mm) in width.

Studs should be positioned roughly as shown.

Double studding is recommended for pivot shower door installations.

Bath cannot be installed without the wall surround.

Width of back wall at top transitions from 60" (1524 mm) at the front to 59-3/8" (1508 mm) in the back corners. Furring strips approximately 1/4" (6 mm) thick should be used at the back corner studs if drywall is to be installed over the nailing flange.

ADA compliant when installed to the specific requirements of these regulations.

1-800-STERLING (1-800-783-7546)

Kohler Co. reserves the right to make revisions without notice to product specifications.
For the most current Specification Sheet, go to www.sterlingplumbing.com.
4-26-2019 00:31 - US